




# HOTSOAK 73


**HOTSOAK SERIES MODEL # AI18AIR7242HS**



**CAN BE USED IN AN UNDERMOUNT APPLICATION**



**Rough-In Plumbing Measurements**



## SPECIFICATIONS:

### General Specifications:

Tub Size	72" X 42" X 24"
	189 cm x 107 cm x 56 cm
Bathing Well	49" long
	24 1/2" wide
	22" interior depth
Shipping Weight	188 lbs. / 85.5 kg
Tub Weight Filled	1359 lbs. / 618 kg
Tub Weight Only	138 lbs. / 63 kg
Gallons to Overflow	163 gal. / 618 L

### Electrical Specifications:

Pump	1/15 HP; 1.3 AMP; 110V
Heater	1.5 kW; 12.5 AMP; 110V
Requirements	20 AMP; 110V, separate circuit required protected w/ Class A GFCI

### STANDARD EQUIPMENT:

- **Aquatic Quality Features:**
- 1.5 kW Inline Maintenance Heater
- Run-Dry Pump with 20-Minute Timer
- 2 Circulation Portal Covers
- Bath-Side On/Off Electronic Button
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Pad Operation
- Slip Resistant Floor
- Extra Deep and Long Bathing Well
- Pre-leveled ABS Support Base
- Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
- Durable, Easy to Clean, Lucite® Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors
- **UL & IAPMO Listed, Factory Tested**
- **Limited Lifetime Warranty**

### OPTIONAL EQUIPMENT:

- Comfort Pillow -- Oval or Rectangle
  - Bolt-On Grab Bars
    - White, Biscuit, Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
  - Lift & Turn Waste and Overflow
    - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, or Oil Rubbed Bronze
  - Cable Drive Waste and Overflow
    - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, Oil Rubbed Bronze, or Color Matched (Bone, White & Biscuit Only)
  - Factory Installed Tile Flange
  - Decorative Rim Kit -- Chrome or Polished Brass
  - Premium Colors
- All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.*

**Fax-On-Demand Document # 1248**



The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building should be measured from the tub; Aquatic Industries, Inc. assumes no responsibility for preparatory work.