



* Available without fast-fill waterfall spout.




Note: Infinity 2 is not a drop in model. A deck must be built around the tub.



NOTE: Please allow for plumbing to extend approx. 3" beyond tub rim.

Rough-In Plumbing Measurements



SPECIFICATIONS:

GENERAL SPECIFICATIONS:

Tub Size	70" x 35 1/2" x 30 3/4" 178 cm x 90 cm x 78 cm
Bathing Well	44" long 20" wide 22" interior depth
Seat	13 1/2" long 15" wide
Maximum Water Depth	18 1/2"
Shipping Weight	356 lbs. / 161 kg
Tub Weight Filled	956 lbs. / 434 kg
Weight w/Equipment	109 lbs. / 49 kg
Gallons to Overflow	102 gal. / 386 L
Gallons to Operate	69 gal. / 261 L

ELECTRICAL SPECIFICATIONS:

Pump	2 HP; 12 AMP; 110V
Inline Heater	1.5 kW; 12.5 AMP; 110V
Requirement	1-15 AMP 2 pole, separate circuit required protected with Class A GFCI
Blower	1 HP; 10.5 AMP; 110V
Requirement	1-15 AMP 1 pole, separate circuit required protected with Class A GFCI

This whirlpool will need to be hard wired to the breaker box. Three outlets will be supplied on the whirlpool.

This unit is not recommended for shower installations.

This unit has a 3/4" female waterfall fill spout connection.

STANDARD EQUIPMENT:

- 16 Hydrotherapy Jets including:**
- 12 Shiatsu Back Jets
 - 2 Rotary Massage Foot Jets
 - 2 Full Size Pressure-Flo Hydrotherapy Jets
- Air Bath System:**
- 1 HP Variable Speed Air Blower with 20-Minute Timer
 - Electronic Control Panel
 - Automatic Purge and Dry Cycle
 - 600 Watt Air Heating System
- Aquatic Quality Features:**
- 2 HP Run-Dry Pump
 - 1.5 kW Inline Maintenance Heater
 - "Quiet Pad" Anti-Vibration Pump Mount for Quiet Pump Operation
 - Shiatsu Electronic Control Panel with Preprogrammed Jet Sequencer
 - Bath-Side Electronic Control Panel with Temperature Display
 - Pulsating Neck Jet Pillow
 - Reclining Lounge Seat and 2 Arm Rests
 - Integrally Molded Fast-Fill Waterfall Spout/Optional
 - please specify on order (valves not included)
 - Chromatherapy
 - Slip Resistant Floor
 - Adjusta-Level Base
 - Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
 - Durable, Easy to Clean, Lucite® Cast Acrylic Surface
 - Available in 8 Standard No-Charge Colors
- UL & IAPMO Listed, Factory Tested Limited Lifetime Warranty**

OPTIONAL EQUIPMENT:

- Available without fast-fill waterfall spout
 - See Price List for Details
- Jet Finish
 - Chrome, Polished Brass, Gold, Polished Nickel or Satin Nickel
- Lift & Turn Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Hand Held Jet - Chrome or Polished Brass
- Premium Colors

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building should be measured from the tub; Aquatic Industries, Inc. assumes no responsibility for preparatory work. www.whirlpoolbath.net 800-894-1022