


STANDARD TRADE IV

MODEL: #3666-STW
ACRYLIC BATH ONLY: #3666-STT

The acrylic whirlpool bath shall be model #3666-STW (3666-STT) as manufactured by Laurel Mountain Whirlpools, Inc. It shall be constructed of .125 thick cast acrylic sheet, backed by layers of polyester resin and fiberglass roving. It will be mounted on a FRP pre-leveled pump-base and two PVC/fiberglass legs. All components will be UL listed and approved. The pump motor will be 1 1/4 horsepower (1 phase, 115V, 60HZ, 3450 RPM, pre-mounted) and the plumbing system will be rigid PVC. The unit will contain 6 multi-directional jets, one air control and a safety suction fitting. Access to pump and plumbing system must be provided by installer in accordance with established plumbing and electrical codes.



ELECTRICAL SPECIFICATIONS - 115V, 20 AMP, GFCI Protected Circuit.



SPECIFICATIONS	WHIRLPOOL	TUB
36" x 66" x 21 1/4" Lip 2		

Water Capacity - Operating Level	44.0 gal.	
- To Overflow	62.0 gal.	62.0 gal.
Approx. Unit Weight	120.0 lbs.	85.0 lbs.
Approx. Shipping Weight	180.0 lbs.	145.0 lbs.

*All dimensions are +/- 3/8" and subject to change without notice. Always pre-measure tub/whirlpool prior to framing above or creating deck installation cut out.



PUMP MOTOR: Standard 1 1/4 HP, Single Phase, 115V, 60HZ, 3425 RPM, Pre-installed (factory)

ELECTRICAL REQUIREMENTS: 115V, 20 AMP, GFCI Protected Circuit.



Bath Environment

www.whirlpoolbath.net
whirlpool@earthlink.net
800-894-1022